iPhone/iPad Stand

Materials: Cotton Fabric 12" x 9" 2-3 cups of rice or buckwheat hulls Pellon Ultra Firm 1 1/4" x 5 3/4" Polyester Fill





1.Start with a piece of fabric that is 12" x 9". Fold in 1/2 and press (6" x 9" size once folded)

2.Sew a 1/4 inch seam at the top, with a 1-1 1/2 "gap, and the side of the folded fabric (refer to black lines). If you would like a loop at the top to hold the cord while charging, insert a fabric or ribbon handle into the seam close to the fold.

3.Fold the fabric so that the side seam is now in the middle at the back. The top will form triangles. I press the seam open for a flat appearance later. Sew along the bottom to form a 1/4 inch seam leaving a 1 - 1 1/2 inch gap (refer to black lines).





4. Through one of the holes, feed the fabric through to invert fabric to show right side. Use a chop stick (or other device to ensure the corners are turned completely).

5.Measure 3 inches from the bottom seam. Mark with chalk on each side. This will be the mark you will use to place the Pellon Ultra Firm Strip.

Feed the Pellon Ultra Firm through the hole at the bottom.

6.Move The Ultra Firm Strip into position with the top aligned with the chalk marks. Pin strip. Sew a border around the strip to ensure it remains in place (refer to black lines).



7. Through the hole at the bottom, stuff with polyester with filling until filled.

8. Hand sew the bottom hole closed using a slip stitch.

9.Fill the main pillow with rice.
Fill as far as you can, approx. 3/4, or
more, fill. You will have room at the top
fill the rest of the space with the polyester
filling.



Report A block

10. Hand stitch top opening close. You now have a complete electronic stand.

ASG on the Web

Wichita ASG site: ASGWichita.org

Wichita ASG Facebook page: www.facebook.com/asgwichita

Wichita ASG email: asgwichita@yahoo.com

National ASG site: www.asg.org

National ASG Facebook page: www.facebook.com/sewingquild

If you would like a loop at the top to hold the cord while charging, insert a fabric or ribbon handle into the seam close to the fold.